

SS25E BLDC Tubular Motor

產品特色 Features

1. 使用直流無刷馬達 Driven by BLDC motor
2. 電子限位 Electronic limit setting
3. 定速同步對齊 Synchronous movement
4. 溫升低 Rotating at low working temperature
5. 尺寸小扭力大 Small volume, big torque
6. 安靜、穩定、低功耗 Silent, stable, low power consumption
7. DC12V 低電壓電源 DC 12V power supply
8. 可納入中控系統 Smart home control compatible



Motor specifications

Model	SS25E-1.5	SS25E-1.5-DCT
Motor type	BLDC motor	
Diameter	25mm	
Input Voltage	DC 12V	
Torque	1.5 Nm	
Rated Speed	35 rpm	
Rated operation time	10 mins	
Dimension	φ25 x 423 mm	
RF receiver	Built-in 433.92MHz	
External Control	X	Dry contact (4C)
Noise	< = 40 dB (A)	
Power	Adapter (DC 12V)	

RF remote control

Model	SSRC05E	SSRC16C
Channel	5 ch multi-control	16 ch multi-control
Frequency	433.92 MHz or 315 MHz	
Max. codes	16millions	
Effective range	10~100 meter	
Battery	CR2430 DC 3V	
Rating Current	< 10μA	
Size	125.5 x 45.5 x 14 mm	
Color	Black, White	
Others	Wall Mount, copy function	